

NEC PX700W

Order Code: 60003183

NEC PX700W Professional Installation Projector

The PX700W a wide format dual lamp installation projector for the highest levels of heavy duty usage, unique picture quality in highest resolution and is the worldwide first projector supporting STv2, compatible with the NEC /Intel OPS standard.

The professional features make it ideal for Rental/Staging, Large Corporate, High Education, Conference Room, Museum and Signage.



DELIVERING GENUINE BENEFITS

Display content that demands attention - with FullHD resolution and superb brightness levels and colour ranges, your viewers will enjoy an outstanding visual experience.

Installation is easy, even in challenging venues - a motorized Lens Shift with vertical and horizontal adjustment makes setting up the perfect installation image easy.

Simple Connectivity - due to the vast number of connectors featured with this projector, including an innovative DisplayPort terminal and a host of networking, analog and digital connection terminals.

Time saving network control - for cost saving convenient maintenance and management of content and scheduling.

OUTSTANDING PERFORMANCE

- **Great picture quality** even in bright ambient light because of high projector brightness and excellent 10-Bit (1.07 billion colours) Hollywood Quality Video signal processing for best colour performance in highest resolution.
- **Best reliability and system stability** because of 2 lamp system and additional colour wheel as standard in the box.
- **Rich installation features** as motorized Lens Shift, Lens Memory, flexible Geometric correction, Light Shutter, Stacking function, built -in Edge Blending function and much more.
- **Best connectivity** supporting nearly all signal sources, as HDMI and even DisplayPort. First projector world wide, which supports STv2 for highest input flexibility as for example Single Board Computer for stand-alone projection.
- **Latest network technology** enables not only many ways of projector control by network but also easy picture transfer.
- **Highest WUXGA resolution** and 10-Bit (1.07 billion colours) Hollywood Quality Video signal processing allows you to enjoy extremely detailed picture quality.



SPECIAL CHARACTERISTICS

Digital 3D Reform™, AMX Beacon, Blanking, 2x Colourwheel, Crestron RoomView, Direct Power-Off Function, Edge Blending Function, Geometric Correction, Help Function, Keystone Correction (H=±40°, V=±30°), LAN control, Lens Memory, Lens Shift (vertical 0.5 max., horizontal ± 0.1 max.), Lens Shutter, OPS module support, OSD with 27 languages, Optional User Logo, Outstanding Multimedia and Network Functions, PJ LINK, Password Security System, Plug&Play W-LAN Option, Powerpoint, Movie, PDF and USB Picture Viewer, RS-232 Control, SNMP, Seamless Switching, Stacking Function, Test Pattern, Windows 7 Network Projector, Hollywood Quality Video Processing for best image quality



Energy Efficiency Complete shut-off switch ; Intelligent Power Management

Ecological Materials ECO packaging ; Minimal use of harmful material

Ecological Standards RoHs compliant; WEEE

Technical Specification NEC PX700W	
IMAGE	
Display	1.65 cm (0.65") DMD Chip - DLP™ Technology
Native Resolution	1280 x 800 (WXGA)
Brightness ¹	7000 ANSI Lumen (approx. 80% in Eco Mode)
Contrast Ratio ¹	2100:1 with DynamicBlack™
Lamp	2-Lamp System (2 x 400 W AC), 2 x 320 Eco Mode
Lamp Life [hrs]	2000 (2500 Eco Mode)
Lens	6 optional bayonet lenses
Projection Factor	depending on lens selection (0.74:1 and 1.25-8.3:1)
Projection Distance [m]	0.8 (NP16FL) - 54 (NP21ZL)
Screen Size (diagonal) [cm]	Minimum: 127 / 50" ; Maximum: 762 / 300" ; (best performance range)
Lense Adjustment	Motorized
Supported Resolutions	1920x1200 (WUXGA) - 640x480 (VGA); 1080i/60; 1080p/60; 1080i/50; 1080p/50; 720p/60; 720p/50; 576i/50; 576p/50; 480p/60; 480i/50
Frequency	Horizontal: 15–108 kHz (RGB: 24 kHz); Vertical: 48 – 120 Hz
CONNECTIVITY	
RGB (analog)	Input: 2 x Mini D-sub 15 pin; 1 x 5BNC, shared with Component Signal (YPbPr) Output: 1 x Mini D-sub 15 pin
Digital	Input: 1 x DisplayPort; 1x HDMI™ (V.1.3) supporting HDCP
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
PC Control	Input: 1 x D-Sub 9 pin (RS-232); 1 x Network (RJ45, W-LAN optional)
Option Slot	Input: 1 x Slot for optional STv2 or HD/SD-SDI Module
USB	2 x Type A (USB 2.0 high speed)
REMOTE CONTROL	
Input:	1 x 3.5 mm Stereo Mini Jack
Remote Control	Aspect Ratio; Auto Adjust; Eco Mode Control; Freeze-function; Full Lense control; HDMI; Help-function; ID Select; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Select (up, down, left, right); Source Select
ELECTRICAL	
Power Supply	100-240 V AC; 50 - 60 Hz
MECHANICAL	
Dimensions (W x H x D) [mm]	504 x 192 x 516 (without lens and feet)
Weight [kg]	19.7
Fan Noise [dB (A)]	43
OPTIONAL ACCESSORIES	
Optional Accessories	Air Filter (NP02FT); Ceiling Mount Kit; HD/SD-SDI Module; Lamp (NP22LP); STv2 PC; Wireless LAN module NP02LM2 (Europe), NP02LM3 (Russia)
Lenses	NP16FL (0.76:1); NP17ZL (1.25-1.79:1); NP18ZL (1.73-2.27:1); NP19ZL (2.22-3.67:1); NP20ZL (3.6-5.4:1); NP21ZL (5.3-8.3:1)
ERGONOMICS	
Safety and Ergonomics	CE; ErP; TÜV GS; RoHS
WARRANTY	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
SHIPPING CONTENT	
Shipping Contents	Projector; IR Remote Control (adressable RD - 455E); Power Cord; Anti-theft cap for LAN Unit; Anti-theft screw for lens; Colourwheel (for exchange); Stacking Holder; Users Manual on CD-ROM; Quick Setup Guide

¹ Compliance with ISO21118-2005