

NEC V311X

Order Code: 60003637

NEC V311X Value Projector

Get the Ultimate 3D Experience with the V311X DLP®Projector. The compact size in combination with light weight makes it easy to place it wherever you need it. With 3100 ANSI lumens brightness and higher contrast this compact projector is recommended for screen sizes of up to 110" diagonal. V311X is Nvidia certified to ensure plug and play operation especially for 3D gaming and 3D photography.

The V311X is the perfect solution for small meeting rooms as well as classrooms.



DELIVERING GENUINE BENEFITS

Control and Monitoring - via RS-232.

Green EcoMode Button - on remote.

Higher Efficiency, Lower Power Consumption - full ErP compliance.

Long Lamp Life - up to 5000 hrs.

Virtual Remote - for direct PC control.

3D ready - future-proof DLP®-Link™ technology with 120Hz and Top/Bottom, 60Hz.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



OUTSTANDING PERFORMANCE

- **Excellent and Brilliant Colours** - due to VIDi technology
- **Contrast 3000:1**
- **High Brightness** 3100 ANSI lumens
- **Quick Start** - Direct Power Off
- **7W Speaker**
- **Carbon Meter** - indicating the reduced amount of CO₂ emissions by the use of ECO mode



SPECIAL CHARACTERISTICS

3D ready DLP®-Link™, 120Hz and Top/Bottom, 60Hz, 6-segment Colour Wheel, Auto Power Start, BrilliantColor™ and VIDI technology, Carbon Savings Meter, Crestron RoomView, Intelligent Power Management, Long Life Lamp, Manual vertical Keystone Correction (V= ±40°), NaViSet Administrator 2, Plug & Play, Quick-Start-/Direct-Power-Off Function, Virtual Remote for direct PC control, 100% recyclable packaging, Downloadable manuals, RoHS compliant, ErP compliant, WEEE



Energy Efficiency Intelligent Power Management

Ecological Materials 100% recyclable packaging;
Downloadable manuals

Ecological Standards RoHS compliant; ErP compliant; WEEE

Technical Specification NEC V311X

| | |
|--------------------------------------|---|
| IMAGE | |
| Projection Technology | 1 x 1.4 cm (0.55") 2x LVDS DMD Chip |
| Native Resolution | 1024 x 768 (XGA) |
| Contrast Ratio ¹ | 3000:1 |
| Brightness ¹ | 3100 ANSI Lumen |
| Lamp | 225 W AC |
| Lamp Life [hrs] | 3000 (5000 Eco Mode) |
| Projection Factor | 1.94 – 2.13 : 1 |
| Projection Distance [m] | 1.2 – 13 |
| Screen Size (diagonal) [cm] / [inch] | Minimum: 76; Maximum: 762 |
| Zoom | Manual |
| Focus Adjustment | Manual |
| Supported Resolutions | Up to 1920x1080 |
| Frequency | Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz |
| CONNECTIVITY | |
| RGB (analog) | Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin |
| HDMI™ | Input: 1 x HDMI™ (Deep Color, Lip sync) |
| Video | Input: 1 x RCA |
| S-Video | Input: 1 x Mini DIN 4-pin |
| Audio | Input: 2 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo for Video and S-Video Output: 1 x 3.5 mm Stereo Mini Jack |
| Control | Input: 1 x D-Sub 9 pin (RS-232) (male) |
| LAN | 1 x RJ45 |
| Video Signals | PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M |
| REMOTE CONTROL | |
| Remote Control | Aspect Ratio; Audio Control; Auto Adjust; Automatic Picture Adjustment; Freeze-function; Help-function; ID set; Keystone Correction; Lamp Mode Control; Magnify-function; Picture Adjust; Picture Mode; Picture Mute; Source Select |
| ELECTRICAL | |
| Power Supply | 100-240 V AC; 50 - 60 Hz |
| Power Consumption [W] | 268 max.; 210 Eco Mode; 0.5 Power Savings Mode |
| MECHANICAL | |
| Dimensions (W x H x D) [mm] | 310 x 95 x 247 (without lens and feet) |
| Weight [kg] | 2.5 |
| Fan Noise [dB (A)] | 33 / 37 (Eco / Normal) |
| ERGONOMICS | |
| Safety and Ergonomics | CE; ErP; TÜV GS; RoHS |
| Speakers [W] | 1 x 7 (mono) |
| WARRANTY | |
| Projectors | 3 years pan-European service |
| Lamp | 6 months, max. 1000 hrs |
| SHIPPING CONTENT | |
| Shipping Contents | User Manual on CD-ROM (Russian Manual in Hardcopy); Projector; IR Remote Control (RD-448E); Mini D-SUB Signal Cable (1.8 m); Power Cord; Quick Setup Guide; Lens Cap |
| OPTIONAL ACCESSORIES | |
| Optional Accessories | 3D Starter Kit (NP01SK3D); DLP-Link 3D Glasses (NP01GL/NP02GL); Lamp (NP18LP); Mouse Receiver (NP01MR); Universal Ceiling Mounts (NP01/02/03/04/05UCM) |

¹ Compliance with ISO21118-2005