



Low Maintenance Laser Projector

FEATURES

- Extraordinarily high brightness at 18,000 ANSI lumens with only one DLP chip system to achieve outstanding performance
- WUXGA resolution and 10,000:1 contrast ratio for clear, crisp and bright projection
- Long lasting laser light source for up to 20,000 hours operations
- Installation flexibility is ensured with 5 optional lenses from 0.84:1 to 7.00:1 throw ratio range
- Designed for heavy duty 24/7 operations with 360° installation angle flexibility
- 3G-SDI & HDBaseT for robustness for long signal transmission
- Built-in multi-screen edge-blending and warping features
- Motorized and wide lens shift range allows easy placement of the projector without distorting the image
- Lens Position Memory to facilitate set up
- New Constant Brightness feature helps reduce blending maintenance with a smart sensor continuously measuring and adjusting the illumination output



Bright 18,000 Lumens Projector with Single Chip DLP

The DU9800Z Single Chip WUXGA Laser Projector delivers 18,000 ANSI Lumens with its laser light source, the DU9800Z delivers up to 20,000 hours of operation. Additionally, the projector presents many benefits to System Integrators due to its small form factor and light weight that enables simple and swift installation. Vivitek offers a new Constant Brightness feature to help reduce blending maintenance and customise brightness with a built-in light sensor inside the projector monitors the level of light. The DU9800Z is very stable projector and is ideally suited to 24/7 operation with low user intervention.



DU9800Z SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	18000 ANSI Lumens
	Native Resolution	WUXGA (1920 x 1200)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	10,000:1
	Keystone Correction	Vertical: +/-40°; Horizontal: +/-60°
Optical	Throw Ratio	5 optional lenses from 0.84:1 to 7.00:1 throw ratio range
	Zoom Ratio	Motorized Zoom & Focus
	Lens Shift (Based on Full Image Height)	Vertical: +/-50%; Horizontal: +/-15%
	Image Size (Diagonal)	depending on lens selection
	Projection Distance	depending on lens selection
	Offset (Based on Full Image Height)	Motorized Lens Shift
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Instant On/Off
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI (x2), Display Port, DVI-D, Component (5 BNC) (RGBHV) , VGA-Out (15pin D-Sub), RJ45 (1: HDBaseT/LAN), RS-232, 3D-Sync (x2: In and Out), Remote Jack(wire remote), 3G-SDI (x2: In and Out)
General	Dimensions (W x D x H)	530 x 693 x 248 mm
	Weight	48 kg
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 1800W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	Lamp free design. Laser light source lasts up to 20,000 hours
	Noise Level	43dB (Normal Mode)
	Standard Accessories	HDMI Cable, User Manual (CD), Lens Cap, Warranty Card (by region), Remote Controller (with battery), AC Power Cord, Remote Control Cable
	Optional Accessories	Remote Control P/N (5041848301)
	Warranty	Large Venue Laser Phosphor Warranty: 5 Year projector / 3 years or 10.000h on the Laser Phosphor illumination source.(Whichever comes first)
	UPC Code	DU9800Z-BK: 813097023377

OPTIONAL LENSES

Lens Name	Standard Lens	Ultra Wide Zoom	Wide Zoom	Long Zoom 1	Long Zoom 2
Aspect Ratio	16:10	16:10	16:10	16:10	16:10
Throw Ratio	1.50-2.00:1	0.84-1.03:1	1.25 - 1.56:1	2.00-4.00:1	4.00-7.00:1
Projection Distance	1.24-21.84	0.7-11.44	0.95-17.47	2.65-41.77	4.38-74.51
Image Size	40-500	40-500	40-500	40-500	40-500
Zoom	1.33	1.22	1.3	2.0	1.70
F Number	2.17-2.65	1.8 - 1.95	2.18-2.66	2.17-2.64	2.20-2.57
Focal Length	31.9 - 42.2 mm	17.95 - 21.93 mm	25.69 - 33.22 mm	42.6 - 84.8 mm	83.93 - 146.85 mm
Part Number	3797886100-SVK (D98-1520)	3797805500-SVK (D98-0810)	3797859900-SVK (D98-1215)	3797893200-SVK (D98-2040)	3797858100-SVK (D98-4070)



© Copyright 2017 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.
DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands. Tel: + tel: +31 20-8003960 | fax: +31 20-8003999 | email: info@vivitek.eu

www.vivitek.eu