



## Display/image

Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	6,500 lumens
ANSI brightness	6,000 lumens
Contrast ratio	100,000:1
ANSI contrast ratio	250
Contrast ratio - dynamic	6,000:1
Contrast ratio - full on/off	1,200:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9, 16:10
Keystone correction - horizontal	20 degrees
Keystone correction - vertical	20 degrees
Uniformity	90%
Screen size	Dependent on lens

## Lamp info

Light source	Laser
LASER life	20,000 hours

## Optical

Throw ratio	Dependent on lens
Projection distance (m)	Dependent on lens
Lens options	BX-CTA16- 0.36 ~ 0.36 BX-CTA15- 0.75 ~ 0.95 BX-CTA01- 0.95 ~ 1.22 BX-CTA06- 1.22 ~ 1.53 BX-CTA03- 1.52 ~ 2.92 BX-CTA13- 2.90 ~ 5.50 BX-CTADOME- Dome lens

## Connectivity

Connections	<b>Inputs</b> 1 x HDMI, 1 x VGA (YPbPr/RGB), 1 x 3D sync, 1 x DVI-D, 1 x HDBaseT <b>Outputs</b> 1 x VGA (YPbPr/RGB), 1 x 3D sync <b>Control</b> 1 x RS232, 1 x Wired remote, 1 x USB-A service, 1 x mini USB service, 1 x RJ45
-------------	--

## General

Noise level (typical)	36dB
PC compatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
2D compatibility	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)
3D compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	Full 3D
Security	Security bar, Kensington Lock
OSD / display languages	11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
24/7 operation	Yes
360° operation	Yes
Operating conditions	5 ~ 40 °C
Remote control	Wired ProAV remote
In the box	AAA Battery, AC power cable 3M, Lens cover, VGA cable 1.8m, User manual CD, Quick start guide

## Networking

LAN - DHCP	Yes
------------	-----

## Power

Power supply	100 - 240V, 50 - 60Hz
Power consumption (standby)	0.5W
Power consumption (max)	650W

## Weight and dimensions

Net weight	17kg
Dimensions (W x D x H) (mm)	484 x 509 x 181

