

1T-C2-750 Dual-PIP DVI-I Scaler is based on TV One's exclusive CORIO®2 technology and has two high quality graphic scalers capable of working at full DVI video rates. The two scalers can be used to convert digital DVI-D or analog DVI-A signals to another format, with full CORIO®2 picture-in-picture flexibility.

DVI-D resolutions up to 1920x1200@60Hz and 1080p are supported along with analog DVI-A (or HD15 via optional adaptor) resolutions up to 2048x2048 at virtually any refresh rate. A wide variety of computer signal formats are available to support PC, Mac and Workstation formats.

The 1T-C2-750 can also be used as a Seamless Switcher device, enabling the user to toggle between the two DVI inputs with instantaneous cuts. Two Still Image Stores are built into the unit which can store ten graphic images each to be used in place of one or both of the DVI-I inputs to add custom logos or backgrounds.

All settings are stored in non-volatile memory and are retained even when power is switched off. Ten user defined presets (two controlled from the front panel) are also available to customize settings for various applications. An On-Screen Display is available to assist in setup. Functions can be controlled via the front panel Push Buttons, Infrared or RS-232. Windows Control Panel software is provided and most third party control systems interface directly with the entire C2 range of products. The unit is housed in a desktop case and an optional rack mount kit holds one or two units.

Variable Zoom to 10X allows you to enlarge any part of the graphic image to fill the entire computer screen and position controls allow you to move around to any area desired. Variable Shrink to as little as 10% allows fitting multiple images next to each other, with full positional controls.

Advanced Features include Genlock, Chromakey, Lumakey, Mixing and Dual PIP. The Key Mode allows computer graphics to be keyed over each other (one input over another). The keyed image may be faded in and out. Due to the 4:4:4 sampling format, precise keying at the pixel level can be achieved. The PIP mode allows either input to be inset into a window over the other input. Both inputs can be placed side by side in a Dual PIP configuration.



Key Features of the 1T-C2-750

- Dual scalers
- 2x DVI-I Inputs
- 2x Internal Still Image Stores
- DVI-D I/O support to 1920x1200, 1080p/60
- DVI-A I/O support to 2048x2048, 1080p/60
- Analog supports RGBHV, RGBS, RGsB & YPbPr
- Control via RS-232, IR or Front Panel
- Windows Control Panel
- Variable Image Zoom to 10X and Shrink to 10%
- Per-pixel or percentage scaling control
- Single and Dual PIP
- Autoset - Automatic analog picture sizing
- Chromakey and Lumakey
- Genlock and Mix
- Optional IR Remote Control Unit
- Optional Single/Dual Rackmount Kit



This symbol on a product indicates that it is powered by CORIO®2 technology, the most flexible video processing engine now available.

Unlike most manufacturers, who use third party chipsets to provide video conversion, TV One has developed its own proprietary technology known as CORIO®2. This frees TV One products from the constraints imposed by third parties and results in an unsurpassed degree of flexibility. Products based on third party chipsets have a feature set frozen at the introduction of the product. Since the CORIO®2 video processing engine is entirely firmware based, it can be upgraded at any time by downloading the latest firmware version from the support website and flash upgrading the unit in the field. This enables new features to be added to units many years after the initial purchase. This "obsolescence insurance" means that a CORIO®2 based product can always be upgraded to the latest version of that model.

Specifications

Inputs	
Signal Type	2x DVI-I via DVI-I Connector
Digital DVI-D Format:	
Max HD Resolution	1080p@60Hz
Max PC Resolution	1920x1200@60Hz
Analog DVI-A Format:	
Max HDTV Resolution	1080p@60Hz
Max PC Resolution	2048x2048
Max Horiz Scan Rate	150KHz
Signal Format	RGBHV, RGBS, RGsB, YPbPr
Sync	TTL Level, 10KΩ, Pos or Neg
Termination	75Ω
R-G-B Level Range	0.5-2.0 Vp-p
Scan Rate Detection	Automatic
Output	
Signal Type	1x DVI-I via DVI-I Connector
Digital DVI-D Format	
Max HD Resolution	1080p@60Hz
Max PC Resolution	1920x1200@60Hz
Analog DVI-A Format	
Max HDTV Resolution	1080p@60Hz
Max PC Resolution	2048x2048
Vertical Refresh Rate	Any to 250Hz
Signal Format	RGBHV, RGBS, RGsB, YPbPr
R-G-B Level	0.7 Vp-p
General	
Size and Position	Automatic via AutoSet or Manual
Image Size	User-Definable Presets
Image Freeze	One Video Frame
Settings Memory	Non-Volatile
Zoom Range	Variable to 10X Zoom
Shrink Range	Variable to 10%
Image Mirroring	Horizontal and/or Vertical
Horizontal Filtering	Full Digital
Conversion Technology	Proprietary – CORIO®2
Frame Rate Conversion	Frame add/drop
Color Resolution	24-bit (16.8 Million Colors)
Sampling Rate	162MHz
Digital Sampling	24-bit, 4:4:4 format
Firmware Memory	Flash, Upgradeable via RS-232
Analog Video Adjust	R-G-B Levels Contrast, Phase

Control Methods	
Local	via Front Panel Buttons & OSD
RS-232 Interface	via D9 Female Connector
Infrared Remote	via IRC-5 Remote Unit
Warranty	
Limited Warranty	2 Years Parts and Labor
Regulatory Compliance	
Main Units	FCC, CE, RoHS
Power Supplies	UL, CUL, CE, PSE, GS, RoHS
Mechanical	
Size (H-W-D)	30x200x90mm(1.18"x7.87"x3.54")
Weight (Net)	0.52 kg (1.14 lbs)
Environmental	
Operating Temperature	0° to +50° C (+32° to +122° F)
Operating Humidity	10% to 85%, Non-condensing
Storage Temperature	-10° to +70° C (+14° to +158° F)
Storage Humidity	10% to 85%, Non-condensing
Power Requirement	
External Power Supply	12VDC@1A
Accessories Included	
1x Operations Manual	1T-C2-750
1x Power Adapter	US, UK or Euro
Product Item Numbers	
1T-C2-750	Dual-PIP DVI-I Scaler
Optional Accessories	
IRC-5	Infrared Remote Control
RM-230	Single/Dual Rackmount Kit
ZDH-2038	DVI Male to 5-BNC Female
ZDH-2040	DVI Male to VGA Female

Panel Drawings

