UNICOL®

Outdoor Housings Digital Signage Solutions

OVERVIEW

Designed for ultra bright screens where brightness levels up to 2500 NITS are commonplace and under certain conditions enclosure temperatures up to 55°C are possible. All are constructed in high grade aluminium for lightness and complete corrosion resistance and utilise high quality temperature control components within.

Our well-proven range of housings can be supplied in this version, from small screen monitors up to the latest 86" large screen sizes. Bolt down, floor standing versions are also available.



KEY FEATURES

- Tailor made for perfect screen fit every time.
- IP53 rated with vandal resistant screen.
- Corrosion free for long life in all weathers.
- Toughened or laminate glass options available.
- Thermostatic internal heating and cooling.
- User-washable particle filters for longevity.
- CE approved.



Tailor made to your choice of screen make and model.



Screen mount incorporated into the housing backplate.



IP53 rated and corrosion free for long life in all weathers.



Suitable for screens with brightness levels up to 2500 NITS.



Thermostatic internal heating and cooling for screen longevity.



Highly adaptable making it ideal for any outdoor environment.



2-way power socket included within housing.



Bolt down, floor standing versions available.



UNICOL®

Outdoor Housings Digital Signage Solutions





ODHO

30 - 32" Outdoor Housing		
Screen Size	30 - 32"	
Dimensions (mm)	dedicated	
Max. NITS Rating	2500	
Max. Temperature	<55°C	
VESA Fixings	dedicated	
Weight Capacity (kg)	dedicated	
Colour Options		
Cost £ (exc. VAT)	ΡΟΑ	



ODH1

33 - 57" Outdoor Housing		
Screen Size	33 - 57"	
Dimensions (mm)	dedicated	
Max. NITS Rating	2500	
Max. Temperature	<55°C	
VESA Fixings	dedicated	
Weight Capacity (kg)	dedicated	
Colour Options		
Cost £ (exc. VAT)	POA	



ODH2

58 - 70" Outdoor Housing		
Screen Size	58 - 70″	
Dimensions (mm)	dedicated	
Max. NITS Rating	2500	
Max. Temperature	<55°C	
VESA Fixings	dedicated	
Weight Capacity (kg)	dedicated	
Colour Options		
Cost £ (exc. VAT)	ΡΟΑ	



ODH3

71 - 80" Outdoor Housing

Screen Size	71 - 80″
Dimensions (mm)	dedicated
Max. NITS Rating	2500
Max. Temperature	<55°C
VESA Fixings	dedicated
Weight Capacity (kg)	dedicated
Colour Options	
Cost £ (exc. VAT)	POA



ODH4

81 - 86" Outdoor Housing

Screen Size	81 - 86″
Dimensions (mm)	dedicated
Max. NITS Rating	2500
Max. Temperature	<55°C
VESA Fixings	dedicated
Weight Capacity (kg)	dedicated
Colour Options	
Cost £ (exc. VAT)	POA

IMAGE COMING SOON

ODH5 87"+ Outdoor Housing

Screen Size	87" +
Dimensions (mm)	dedicated
Max. NITS Rating	2500
Max. Temperature	<55°C
VESA Fixings	dedicated
Weight Capacity (kg)	dedicated
Colour Options	
Cost £ (exc. VAT)	ΡΟΑ